

Burroughs

Payment Systems

Burroughs EF375 Printer

Compact Multifunction Teller Receipt Printer



-
- Optimized features and small footprint perfect for busy counters
 - Easy paper loading
 - High speed logic seeking print head
 - OPOS compliant
 - High reliability

Get receipt, slip and validation printing all in one small, space saving package.

The Burroughs EF375 makes the most efficient use of limited space, and with a clamshell mechanism that simplifies roll paper replacement and a movable platen that facilitates slip insertion, this printer also boasts excellent paper handling.

Handles Many Types of Media

This Burroughs high-quality multifunction printer can be used for a variety of applications. The EF375 prints receipts, slips, journals, and can also perform validation printing. Printing up to 58 lines on slip paper and 16 lines of validation printing, this printer handles the needs of almost any environment.

User Friendly Design and Use

The moveable platen, paper loading lever switch and clamshell mechanism makes slip insertion, roll paper loading and routine maintenance quick and easy. Add to this an ASB (Automatic Status Back) function to keep operators constantly informed of printer status.

Small Footprint

With a height of just 145 mm (5.7") and a footprint of only 186 x 327 mm (W x D) {7.3 x 12.9"}, the EF375 is one of the smallest 1.5 station printers available, allowing you to use your limited counter space to its maximum efficiency.

Compatibility

Highly expandable and easy upgrades to ensure efficient use of current software assets. Using either the default driver or one of the Burroughs Payment Systems partner teller printer drivers will allow you to reduce time and money spent on developing teller receipt printer application software.

Superb Reliability

Burroughs world-renowned quality and reliability are reflected in every component and mechanism of the EF375, ensuring our products are unsurpassed in performance and dependability.

EF375 Specifications

Features	Burroughs EF375 Printer
Print Method	9-pin, serial impact dot matrix
Print Font	5 x 9 / 7 x 9
Column capacity	33 / 40 columns
Character size	1.56 x 3.1 mm (W x H) / 1.24 x 3.1 mm (W x H) [0.061 x 0.122" / 0.049 x 0.122"]
Character set	95 Alphanumeric characters, 32 International characters, 126 x 8 graphic characters
Print Speed	Approx. 3.5 lps (40 columns, 16 cpi) Approx. 5.4 lps (20 columns, 16 cpi)
Data Buffer	4 KB or 40 bytes
Interfaces	RS-232C
Paper Dimensions	Receipts or Journal : 76 +/- 0.5 x diameter 83 mm {2.99 +/- 0.02 x diameter 3.27"} Slip: 70 to 182 x 160 to 257 mm (W x L) {2.76 to 7.17 x 6.30 to 10.12"} Validation: 135 to 182 x 70 to 257 mm (W x L) {5.31 to 7.17 x 2.76 to 10.12"}
Paper Thickness	Receipts or Journal: 0.06 to 0.085 mm/sheet {0.0024 to 0.0033} (Total thickness: 0.16 mm {0.0062"} or less) Slip: 0.09 to 0.12 mm/sheet {0.0035 to 0.0047} (Total thickness: 0.09 to 0.31 mm {0.0035 to 0.0122"})
Copy Capability	Receipts or Journal: One original and one copy Slip: One original and two copies
Inked Ribbon	ERC38B (Black)
Ribbon Life	Black: 3,000,000 characters
Power Supply Voltage	24 VDC +/- 10%
Current Consumption	Approx. 1.4 A (mean)
D.K.D. Function	2 drivers
Reliability	MTBF 180,000 hours BCFB 29,000,000 lines
Overall Dimension	186 x 327 x 145 mm (W x D x H) {7.3 x 12.9 x 5.7"}
Mass	Approx. 4.0 kg {8.8 lb}
EMI Standards	VCCI class A, FCC class A, CE marking
Safety Standards	UL, CSA

Inch values are approximate.
cpi: characters per 25.4 mm (characters per inch)
lps: lines per second

For more information or to order Burroughs products, please visit www.Burroughs.com
or www.Burroughsstore.com or call 1-800-448-1424 in the U.S.
or 1-800-387-6127 in Canada

Specifications are subject to change without notice.

©2010 Burroughs Payment Systems, Inc.

All rights reserved.

Burroughs is registered trademark licensed to Burroughs Payment System, Inc. in the United States and other countries. All other brands and products referenced herein are acknowledged to be trademarks or registered trademarks of their respective holders.

Printed in the United States of America 04/10

BL100128-200